ANNUAL CCR SURFACE IMPOUNDMENT INSPECTION:			
Facility Name:		Cleco Dolet Hills Power Station	
Address:		963 Power Plant Rd. Mansfield, LA	
Surface Impoundment Name :	Ash Basin No. 1	Owner:	Cleco Power LLC
Surface Impoundment ID:	P-0037	Operator:	Cleco Power LLC
Nearest City:	Mansfield	Parish:	DeSoto
Inspector:		James C. Van Hoof, P.E.	
Company:		Providence Engineering & Environmental Group LLC	
Date of Inspection:		12/18/2020	
Weather at Time of Inspection:		Sunny, Cool	
RECORDERON OF THE OPERATION OF THE OUREAGE IMPOUNDMENTS			

#### DESCRIPTION OF THE OPERATION OF THE SURFACE IMPOUNDMENTS:

The bottom ash and economizer ash are mixed with water and sluiced in a slurry form to either of the two Ash Basins. Ash slurry pipelines within each basin enable the discharge of the slurry at multiple points within each basin. The discharge into each respective basin begins at the end of the pipeline network at the point furthest from the weir box, and proceeds toward the front of the pond. As a basin fills with ash, sections of the discharge pipe are removed as needed so that ash can be uniformly deposited and the storage capacity of each basin fully utilized. The ash-laden water is retained in the Ash Basins for a period of time sufficient to settle most of the suspended particles out of the sluice water. Both Ash Basins capture and retain rainfall runoff from drainage areas upstream of the basin dikes.

Bottom ash is sluiced to Ash Basins No. 1 and No. 2. When one basin is in service collecting ash which settles out of the recirculating sluice water, the other basin is drained and cleaned, as needed.

GENERAL			
Owner Contact:	Kaleb Atkins	Phone:	318-682-8562
Plant Manager:	Marty Robinson	Phone:	318-682-8523
Dam Status:	Operational	Year Built:	1984
Latitude:	32° 01.82' N	Longitude:	93° 33.68' W
Dam Size:	400 Acre-Feet @ 253.5 ft.		
Bottom of Pond Elevation	220 ft. NAVD 88	Top of Dike Elevation:	256 ft. NAVD 88
Low Operating Level Elevation:	230 ft. NAVD 88	High Operating Level Elevation:	251 ft. NAVD 88
High Operating Level Storage:	330 acre-feet @ 251.0 ft. NAVD 88		
Maximum Storage:	400 acre-feet @ 253.5 ft. NAVD 88		
Maximum Surface Impoundment Area:	33.18 Acres		
Offsite Drainage Area:	Discharges to Secondary Pond, thence to Mundy Bayou		
Spillway/Overflow Structure Type:	Internal adjustable concrete stoplog overflow weir structure that drains through		
	culvert to Secondary Pond. Also, an auxiliary overflow spillway drains to the		
	Secondary Pond. The auxiliary spillway has 6" riprap on the bottom and sides of the		
spillway up to elevation 256.0 NAVD 88.			

QUESTIONS FOR OWNER'S REPRESENTATIVE	
Construction Plans Available?	✓ Yes No
Site Facility Map Available?	✓ Yes No
Operations and Maintenance Manual Available?	✓ Yes No
Emergency Action Plan Available?	✓ Yes No
Recent Modification or Improvements?	Repaired exterior western levee in 2014.
	Installed new level gauge in 2016.
Are Routine Inspections Completed?	✓ Yes No
Is Routine Maintenance Completed?	✓ Yes No
Is There Vehicle Access to the Pond?	✓ Yes No
Is Access Available During Heavy Rains?	✓ Yes No
Are Routine Inspection Logs Kept On-site?	✓ Yes No
Offsite Drainage Area:	Discharges to Secondary Pond, thence to
	Mundy Bayou
Spillway/Overflow Structure Type:	Internal adjustable concrete stoplog overflow weir structure that drains through culvert to Secondary Pond, thence to Mundy Bayou. Also, an auxiliary overflow spillway drains to the Secondary Pond. The auxiliary spillway has 6" riprap on the bottom and sides of the spillway up to elevation 256.0 NAVD 88.

PHYSICAL DAM FEATURES – RESERVOIR:		
Staff Gauge Type:	Level Gauge Indicator	
Staff Gauge Elevation at Time of Inspection:	234.0 ft. NAVD 88	
Normal Operating Elevation:	246.0 ft. NAVD 88	
Typical Operation:	Discharges to Secondary Pond, thence to Mundy Bayou	
Are there any visible swirls?	☐ Yes ✓ No	
If yes, describe (size, location, etc.)		
Is there excessive CCR buildup in the surface impoundment?	☐ Yes ✓ No	
If yes, describe (size of area, location, severity, etc.)		
Approximate volume of Impounded water at time of	220 acre-feet	
inspection:		
Approximate volume of CCR at time of inspection:	235,000 cubic yards	
Findings:	The reservoir was inspected and appeared to be in satisfactory condition. No corrective actions are required at this time.	
Other observations on the reservoir:	None	

PHYSICAL DAM FEATURES – INTAKE WORKS:	
Number of Intakes:	Four
Description (1):	Primary Bottom Ash Sluice Pipe
Size and Type:	12 Inch Steel Pipe
Control:	Controlled by Pumps at Plant
Can Flow be Shutoff or Bypassed:	✓ Yes No
Description (2):	Chemical Sump Pipe
Size and Type:	9 Inch Fiberglass/PVC
Control:	Valve
Can Flow be Shutoff or Bypassed:	✓ Yes  No
Description (3):	Intermittent Treated Sanitary Discharge
Size and Type:	4 Inch HDPE
Control:	Controlled by Pumps at Sanitary Unit
Can Flow be Shutoff or Bypassed:	✓ Yes No
Description (4):	Boiler Area Sump Water
Size and Type:	12 Inch Steel Pipe
Control:	Controlled by Pumps at Plant
Can Flow be Shutoff or Bypassed:	✓ Yes No
Is the in-flow piping free of debris and otherwise unobstructed?	✓ Yes  No
If no, describe (type of debris, reason for obstruction, etc.)	
Describe the quality of discharge from hydraulic structure	The inflowing water contains bottom ash which is sluiced
(turbidity, depth, etc.)	out of solution.
Findings:	The intake works were inspected and appeared to be in satisfactory condition. No corrective actions are required at this time.
Other observations on the intake works:	None

PHYSICAL DAM FEATURES – OUTLET WORKS:	
Number of Outlets:	One
Outlets/Culvert Pipe Sizes:	36 Inches
Type of Pipes:	Corrugated Metal Pipe from internal overflow weir structure to
	Secondary Pond.
Control:	Adjustable concrete stoplog overflow weir structure
Can Flow be Shutoff or Bypassed:	✓ Yes No
Describe the overall condition of the hydraulic structure: (Check	✓ Functioning Normally
all that apply)	☐ Not Functional
	☐ Deteriorated
	☐ Damaged
	Adequate
	Inadequate Other:(describe)
Is there evidence of erosion around the hydraulic structure?	☐ Yes ✓ No
If yes, describe (size of area, location, severity, etc.)	
Is the hydraulic structure outlet flowing freely and unobstructed?	✓ Yes  No
If no, describe (type of debris, reason for obstruction, etc.)	
Describe the quality of discharge from the hydraulic structure	The outflowing water is relatively clear and discharges to the
(turbidity, depth, etc.)	Secondary Pond.
Findings:	The outlet works were inspected and appeared to be in
	satisfactory condition. No corrective actions are required at
	this time.
Other observations on the outlet works:	None
	L

SLOPE PROTECTION – EXTERIOR SLOPES:	
Describe the vegetation on the exterior slope:	Recently Mowed
(Check all that apply)	☑ Good Cover
	☐ Sparse
	Other: (describe)
Is there any erosion on the exterior slope?	Yes V No
If yes, describe (size of area, location, severity, etc.)	
Is there any erosion protection on the exterior slopes?	Yes V No
(e.g. riprap, other)	
If yes, describe (riprap - adequate, inadequate, etc.)	
Are there any Crack/Rills Observed?	☐ Yes ☑ No
If yes, describe (size of area, location, severity, etc.)	
Are there any Sinkholes Observed?	☐ Yes ☑ No
If yes, describe (size of area, location, severity, etc.)	
Are there any trees on the slopes?	☐ Yes ☑ No
If yes, describe (type of vegetation, size, location, etc.)	
Findings:	The exterior slope was inspected and appeared to be in satisfactory condition. No corrective actions are required at this time.
Other observations on the exterior slopes:	None

SLOPE PROTECTION – INTERIOR SLOPES:		
Describe the vegetation on the interior slopes:	Recently Mowed	
(Check all that apply)	Good Cover	
	Sparse	
	Other: (describe)	
Is there any erosion on the interior slope?	☐ Yes ☑ No	
If yes, describe (size of area, location, severity, etc.)		
Is there any erosion protection on the interior slopes?	☐ Yes ☑ No	
(e.g. riprap, other)		
If yes, describe what type and it's condition (riprap - adequate, inadequate, etc.)		
Are there any Crack/Rills Observed?	Yes V No	
If yes, describe (size of area, location, severity, etc.)		
Are there any Sinkholes Observed?	☐ Yes ☑ No	
If yes, describe (size of area, location, severity, etc.)		
Findings:	The interior slope was inspected and appeared to be in	
	satisfactory condition. No corrective actions are required	
	at this time.	
Other observations on the interior slopes:	None	

SLOPE PROTECTION – ABUTMENT/TOE:	
Describe the vegetation on the Abutment/Toe:	Recently Mowed
(Check all that apply)	Good Cover
	☐ Sparse
	Other: (describe)
Is there any erosion on the abutment/toe?	☐ Yes ☑ No
If yes, describe (size of area, location, severity, etc.)	
Is there any erosion protection on the abutment/toe?	☐ Yes ☑ No
(e.g. riprap, other)	
If yes, describe what type and it's condition (riprap - adequate, inadequ	uate, etc.)
Are there any Crack/Rills Observed?	☐ Yes ☑ No
If yes, describe (size of area, location, severity, etc.)	
Is there any Seepage Observed:	☐ Yes ☑ No
If yes, describe (size of area, location, severity, etc.)	
Findings:	The abutment/toe was inspected and appeared to be in
	satisfactory condition. No corrective actions are required
	at this time.
Other observations on the abutment/toe:	None

SURFACE IMPOUNDMENT CREST:		
Describe the vegetation on the crest: (Check all that apply)	Recently Mowed	
	✓ Good Cover	
	Sparse	
	✓ Other: (describe) Gravel	
Is there a road or driveway on the crest?	✓ Yes  No	
If yes, describe (good condition, numerous cracks, etc.) Good Condition		
Are there any ruts, depressions, or holes on the crest?	Yes ✓ No	
If yes, describe (size, location, etc.)		
Are there any cracks on the crest?	Yes V No	
If yes, describe (length and width, location and direction of cracking, et	c.)	
Are there any trees or other undesired vegetation on the crest?	☐ Yes ☑ No	
If yes, describe (size, location, etc.)		
Are there any sinkholes?	Yes V No	
If yes, describe (size, location, etc.)		
	The crest was inspected and appeared to be in satisfactory condition. No corrective actions are required	
	at this time.	
Other observations on the crest:	None	

PHYSICAL DAM FEATURES – SPILLWAY/OVERFLOW STRUCTURE TYPE:		
Type (1):	Internal Concrete Structure with Adjustable Overflow Weir	
Slope Protection:	Encased in concrete	
Approach:	Concrete structure within ash sluice water. Vegetation on the northern side has good cover.	
Erosion:	None observed	
Vegetation:	Vegetation on the northern side of the structure has good cover.	
Findings:	The overflow structure was inspected and appeared to be in satisfactory condition. No corrective actions are required at this time.	
Other observations on the overflow structure:	None	
Type (2):	Auxiliary Spillway	
Slope Protection:	6" rip rap up to elevation 256.0 NAVD 88.	
Approach:	6" rip rap up to elevation 256.0 NAVD 88.	
Erosion:	None observed	
Vegetation:	Grass vegetation on top of the rip rap as it enters the Secondary Pond.	
Findings:	The spillway was inspected and appeared to be in satisfactory condition. No corrective actions are required at this time.	
Other observations on the spillway:	None	

DOCUMENTATION REVIEW:	
Weekly Inspections Reviewed:	✓ Yes □ No
Findings: Vegetation maintenance.	
Monthly Instrument Inspections Reviewed:	✓ Yes  No
Findings: No issues.	
Groundwater Monitoring:	Monitoring wells are in-place.
Drawings Reviewed:	✓ Yes  No
Are there any changes in the geometry of the surface	Yes V No NA
impoundment structure since the previous inspection?	
If yes, describe (size, location, etc.)	
Other observations:	None



**Site Name:** Dolet Hills Power Station – Ash Basin No. 1

Site Location: Mansfield, DeSoto Parish, LA

Date: December 18, 2020

## Ash Basin No. 1

## Direction:

Southeasterly

#### Comments:

Overflow weir structure with concrete stoplogs. Level gauge attached to structure.



## Ash Basin No. 1

# Direction:

Westerly

## **Comments:**

Internal slope of northern levee.





**Site Name:** Dolet Hills Power Station – Ash Basin No. 1

Site Location: Mansfield, DeSoto Parish, LA

Date: December 18, 2020

## Ash Basin No. 1

# **Direction:**

Westerly

## **Comments:**

External slope of northern levee.



## Ash Basin No. 1

## Direction:

Northerly

#### **Comments:**

Internal slope of western levee.





**Site Name:** Dolet Hills Power Station – Ash Basin No. 1

Site Location: Mansfield, DeSoto Parish, LA

Date: December 18, 2020

## Ash Basin No. 1

## Direction:

Easterly

## Comments:

Bottom ash sluicing structure in surface impoundment.



## Ash Basin No. 1

## Direction:

Southerly

### Comments:

Access road on western levee.





**Site Name:** Dolet Hills Power Station – Ash Basin No. 1

Site Location: Mansfield, DeSoto Parish, LA

Date: December 18, 2020

## Ash Basin No. 1

# Direction:

Northerly

## Comments:

Western exterior levee slope.



# Ash Basin No. 1

# Direction:

Southerly

## **Comments:**

Western exterior levee slope.



# ASH BASIN NO. 1 CCR ANNUAL INSPECTION

#### PROFESSIONAL ENGINEER CERTIFICATION

I hereby certify that I have inspected Cleco's Dolet Hills Power Station Ash Basin No.1 in accordance with the Annual CCR Inspection requirements. This inspection has determined that the design, operation, and maintenance of the Ash Basin No. 1 is in accordance with generally accepted engineering standards and is adequate for the facility.

James C. Van Hoof			
Name			OF LOUIS
24630	LA		The Carlotte
Registration No.	State		JAMES C. VAN HOOF
James C. Van Hoof, P.E.		JAMES C. VAN HOOF REG. No. 24630 REGISTERED PROFESSIONAL ENGINEER	
			IN ENCINEERING
Signature			
1-14-2021	_		
Date			(Seal)

This inspection was conducted to assess the general overall condition of the reservoir/dam, identify visible deficiencies, and recommend areas for monitoring, and corrective actions. The inspection is based only on visible features/areas of the dam on the day of inspection. The owner should verify the findings of this report and take corrective actions. This inspection does not relieve the owner/operator from their responsibility to conduct routine inspections, maintenance, repairs, modifications, monitoring, and documentation.